SPECIFICATION SHEET
Date: 18 / 03 / 11
Revision 7

Consequence

Upshot / Sequel / Obscura / Edit

CE
07
0338-CPD-1004
EN 14041:2004
Cfl-s1
NPD
EN 1307

Construction	Tufted, Luxury Textured Loop Pile
Face Fibre	100% Milliken-Certified WearOn® Type 6,6 Nylon
Stain Repel / Stain Resist / Soil Release	StainSmart®
Antimicrobial	AlphaSan® Built-In Protection
Finished Face Weight	915 g/m^2
Gauge	40 / 10 cm
Rows	47.9 / 10 cm
Tuft Density	191,600
Finished Pile Height	6.3 mm avg
Standard Backing	Comfort Plus^2 ® recycled polyurethane cushion backing Available with TractionBack® on request
Nominal Total Thickness	12.8 mm
Tile Size	457.2 x 457.2 mm
Nominal Total Weight	4,400 g/m^2
Tiles per Box	12 (2.5 m²)

PERFORMANCE	
Flammability (Euro classification EN13501:1-2002)	Class Cfl – s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot metal nut BS4790)	Low radius of Char
Use Classification (EN1307)	Class 33 Heavy Commercial Use
Static Electricity (ISO 6356)	≤ 2.0 KV, Permanent Conductive Fiber
Impact Sound (ISO 140-8)	33 dB
Sound absorption (ISO 354)	0.33 Class D

ENVIRONMENTAL	85% Recycled content cushion backing 10% Recycled content by total product weight Manufactured using electricity from renewable sources Carbon Neutral certification GUT & CRI Green Label Plus certified for indoor air quality BRE Certification – ENP 422

Design Copyright – Milliken & Company
This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending.
Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

1096 112721

Guarantees:

15 year wear guarantee

Lifetime Antistatic guarantee

Latent Defects guarantee

Installation Method:

Upshot & Sequel - Half drop



Sequel - Monolithic



Edit - Half drop



Obscura - Monolithic