



POWERFUL DESIGN FOR ANY SETTING
LEVOLAN SLIDING DOOR SET

GEZE Levolan 150

The design fitting for all-glass sliding doors

With its compact dimensions, GEZE Levolan offers a virtually invisible clamp fitting for single, multi-leaf and synchronous all-glass doors. The pane is guided directly in the fitting – the suspension parts are therefore virtually invisible, additional covers are not required. The linear design adapts to the design of any environment. The running rail is only 63 mm high, clamping jaws enable the installation of glass elements without the need to machine or work the glass. The high-quality bearings and maintenance-free running gear ensure that easy and smooth running movement of the glass elements with little applied force. All visible parts are available with silver coloured anodised aluminium or stainless steel coloured surfaces.

GEZE Levolan 150



Application range

- For ESG 8, 10 and 12 mm glass elements as well as VSG up to 12.76 mm (with additional VSG kit) up to a weight of 150 kg
- For all single, multi-leaf and synchronous sliding doors
- With or without fixed panel
- For wall attachment and ceiling installation
- Can even be installed in confined spaces

Technical data

Product features	GEZE Levolan 150
Door material	Glass
Leaf weight (max.)	150 kg
Number of leaves	1-leaf, 2-leaf
Corrosion protection class	2
Type of installation	Wall installation , Ceiling installation
Telescope	-
Automated	-
Fixed panel	•
Draw-in damping	•

- = YES
- = NOT AVAILABLE

Classification to EN 1527:1998

GEZE Levolan 150								
Category of use	Durability	Door weight	Fire resistance	Safety	Corrosion resistance	Security	Category of door	Initial friction
-	6	3	0	-	2	-	1	3

A DESCRIPTION OF THE CLASSES IS GIVEN AT THE END OF THE CATALOGUE.


GEZE Levolan 150 SoftStop

Strong design – gently damped

Levolan offers the special advantage of effortlessly holding sliding glass door elements with clamping jaws and, apart from the holes necessary for mounting the handles, without any glass working or machining, up to a weight of 150 kg. With Levolan SoftStop, the new variant with draw-in damping, sliding glass door elements up to 80 kg can be installed. All-glass sliding doors with Levolan can be installed with ESG with 8, 10 and 12 mm thickness; VSG can be installed with an additional set. The height adjustability of the door leaf via the roller carriage enables optimum adjustment of the sliding door to the circumstances in the building. The easy and smooth running rollers and roller bearings ensure maximum sliding ease and a long life.

With the draw-in damping, GEZE Levolan is now equipped with additional safety and comfort. Around 10 cm before the end of the slide guide damping gently brakes the closing movement of the door. The sliding door leaves are then automatically guided, gently and virtually silently, into the end position. Levolan SoftStop prevents knocking against the frame or buffer. An entrapment hazard is practically excluded. Levolan SoftStop can be inexpensively retrofitted and adapts the sliding door to changing user needs, e.g. of children or senior citizens. Two-sided draw-in damping for Levolan SoftStop is available for narrow standard door leaf widths from 976 mm. Levolan SoftStop corresponds to the highest classes of EN 1527.

GEZE Levolan 150 SoftStop



Application range

- For ESG 8, 10, 12 mm and VSG up to 12.76 mm with additional VSG gluing kit (not including glass preparation)
- For all single and multi-leaf sliding doors
- Simple, direct ceiling mounting or fixing onto the wall and ceiling using an angle bracket
- Damped on one or both sides
- Due to its smooth running it is particularly suitable for doors in the home and office

Technical data

Product features	GEZE Levolan 150 SoftStop
Door material	Glass
Leaf weight (max.)	80 kg
Number of leaves	1-leaf, 2-leaf
Corrosion protection class	2
Type of installation	Wall installation , Ceiling installation
Telescope	-
Automated	-
Fixed panel	•
Draw-in damping	•

- = YES
- = NOT AVAILABLE