

Ecophon Hygiene Foodtec™ A C3

Ecophon Hygiene Foodtec A C3 is a wall to wall, sound-absorbing ceiling system intended for environments where there is risk for contaminations, and where frequent cleaning is required. This system is recommended where humidity levels are occasionally high. Examples of applications: the food and beverage industries, restaurants and catering kitchens.


The system consists of Ecophon Hygiene Foodtec A tiles, which have a core of high density, 3rd generation glass wool and a painted stain protected Akutex HS surface. The back and the edges are painted. The tile is designed to be demounted and cleaned on a regular basis. The supporting structure is a corrosion protected exposed Connect T24

C3 grid of specially treated steel with a high corrosion resistance. The weight of the system is approximately 3,5 kg/m² (20 mm) and 5 kg/m² (40 mm). The tiles should be secured to the grid with Connect Hygiene clips in order to withstand pressure during cleaning and to minimise.



Only, Landskrona, Sweden

SYSTEM RANGE




Size, mm	600x600	600x600	1200x600	1200x600
T24	•	•	•	•
Thickness	20	40	20	40
Inst. Diag.	M249	M249	M249	M249




Hygiene Foodtec A tile



Hygiene Foodtec A system



Hygiene Foodtec A C3 section with
Connect Hygiene clip 20



Connect Tape applicator for sealing
of cut edges




Acoustic

Sound Absorption:

Test results according to EN ISO 354. Classification according to EN ISO 11654.

α_p Practical sound absorption coefficient



— Hygiene Foodtec A 20 mm, 200 mm o.d.s.

- - - Hygiene Foodtec A 40 mm, 200 mm o.d.s.

o.d.s = overall depth of system

THK mm	o.d.s. mm	α_p Practical sound absorption coefficient						α_w	Sound absorption class
		125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz		
20	200	0,55	0,80	0,85	0,85	1,00	0,95	0,90	A
40	200	0,55	0,70	0,85	0,95	0,95	0,85	0,90	A



Accessibility

The tiles are demountable. Minimum demounting depth according to installation diagram. The tiles are secured using Hygiene Clip 20 to allow for effective in-situ cleaning. The clips are easily removable from above the ceiling. A tightly sealed, easy-to-open Hygiene Inspection hatch is available to simplify access to the ceiling void.



Cleanability

Daily dusting and vacuum cleaning. Weekly wet cleaning on all surfaces and high-pressure washing twice a year. Can withstand the use of common disinfecting chemicals.



Visual appearance

White 500, nearest NCS colour sample S 0500-N, 84% light reflectance.



Influence of climate

The tiles withstand a permanent ambient RH up to 95% at 30°C without sagging, warping or delaminating (ISO 4611). A higher temperature/moisture is permissible during washing as stated above. Microbiological growth class 0 according to ASTM G 21-96. The grid and accessories meet the demands of corrosion class C3 according to EN ISO 12944-2.



Indoor Climate

Certificate / Label

Europe

EN
13501-1

Can be used in rooms classified as ISO class 4 according to ISO 14644-1.



Environmental influence

Certificate / Label

Europe

EN
13501-1

Glass wool core utilizing 3RD Technology. In combination with Master Rigid system Extra Bass is granted the Nordic Swan eco-label. Fully recyclable.



Fire safety

Country

Europe

Standard

EN 13501-1

Class

A2-s1,d0

The glass wool core of the tiles is tested and classified as non-combustible according to EN ISO 1182. The systems are classified as fire protective covering according to NT FIRE 003.



Mechanical properties

See table about Max live load and Min load bearing capacity and Functional demands, Mechanical properties at www.ecophon.com.



Installation


Installed according to installation diagrams, installation guides and drawing aid. Cut panels must be sealed with Connect sealing tape using the Connect Tape applicator, or Connect Edge sealant. Penetrations must be sealed with a suitable sealant.



CE

2,9 kg equivalent CO₂ / m² according to EPD

INSTALLATION DIAGRAM (M249) FOR ECOPHON HYGIENE FOODTEC A C3



© Ecophon Group


QUANTITY SPECIFICATION (EXCL. WASTAGE)

		Size, mm	
		600x600	1200x600
1	Hygiene Foodtec A	2,8/m ²	1,4/m ²
2	Connect T24 Main runner C3, installed at 1200 mm centres	0,9m/m ²	0,9m/m ²
3	Connect T24 Cross tee C3 9102, L=1200 mm, installed at 600 mm centres	1,7m/m ²	1,7m/m ²
4	Connect T24 Cross tee C3 9103, L=600 mm	0,9m/m ²	-
5	Connect Adjustable hanger C3, c1200 (max distance from wall 600 mm)	0,7/m ²	0,7/m ²
6	Connect Hanger clip (not to be used in swimming hall environments)	0,7/m ²	0,7/m ²
7	Connect Inspection hatch C3	as required	as required
8	Connect Hygiene clip 20	11/m ²	7/m ²
9	Connect Hygiene clip 40	11/m ²	7/m ²
10	Connect Channel trim C3 (for 20 mm thickness)	as required	as required
11	Connect Channel trim C3 3465 (for 40 mm thickness)	as required	as required


Δ Min. overall depth of system: 150 mm

δ Min. demounting depth 20 mm: 150 mm


δ Min. demounting depth 40 mm: 170 mm



See Quantity specification



Arrangement of clips



Clips for keeping tiles in position

Size, mm	Max live load [N]	Min load bearing capacity [N]
600x600	50	160
1200x600	50	160

Live load/load bearing capacity