

Interface®

Equal Measure 553

Product definition

Tufted Patterned Structured Tip Sheared Tile

Pile Material	100% Recycled Solution Dyed Nylon
Pile Yarn Weight	1221g/m ² ± 5%
Total Weight	5069g/m ² ± 5%
Pile Height	6.1 mm ± 0.5 mm
Total Thickness	9.6 mm ± 0.5 mm
Gauge/Ends per 10cm	1/10 - 39.4
Tufts per m2	200,940 ± 5%
Backing Type	Graphlex®
Wear Classification	EN 1307 33 Heavy Contract

Radiant panel (EN ISO 9239/1) Euroclass Cfl s1 (EN ISO 13501)

Dimensional Stability ≤ 0.2% (EN 986)

Impact Sound Insulation (ΔLw) 27 dB (EN ISO 10140-3)

Rating of Sound Absorption α_w 0.20 (EN ISO 11654)

Sound Absorption

125Hz 0.01	250Hz 0.03	500Hz 0.08	1000Hz 0.17	2000Hz 0.33	4000Hz 0.48	(EN ISO 354) α _s
----------------------	----------------------	----------------------	-----------------------	-----------------------	-----------------------	--------------------------------

Style number 7889 3m² - 12 Tiles per Box (25 cm x 100 cm ± 0.20%)

EN 14041

CE

DOP: 1037/122925

textile floor covering

EN 1307

990B5AD0

www.pro-din.info

install with TacTiles®

ASHLAR

HERRINGBONE

33

Cfl-s1

0S

27 dB

0.20

≥ 7

≥ 2.4

Interface Europe Ltd reserve the right to change or modify specifications

www.interface.com



Mission Zero:
our promise to eliminate any
negative impact our company
may have on the environment
by the year 2020.