



- NOTES
1. IT IS THE CLIENTS RESPONSIBILITY TO ENSURE THE STRUCTURE IS CAPABLE OF ACCEPTING THE FIXINGS SHOWN AND SUPPORTING THE DOOR / PRODUCT WEIGHT WHILST AT REST AND DURING OPERATION.  
APPROX. DOOR WEIGHT = \_\_\_\_\_ kg.
  2. BOLTON GATE CO. LTD. RECOMMEND THAT FULL ACCESS TO THE SHUTTER BOX BE PROVIDED ACROSS THE OPENING FOR MAINTENANCE/REPLACEMENT PURPOSES. IF FULL ACCESS IS NOT PROVIDED BOLTON GATE CO LTD WILL NOT ACCEPT ANY CHARGES ASSOCIATED WITH THE GAINING OF ACCESS TO FACILITATE THE MAINTENANCE OR REPLACEMENT OF ANY SHUTTER COMPONENTS.
  3. ELECTRICAL EQUIPMENT TO SUIT A 415V. 3Ph. AND NEUTRAL 50Hz. SUPPLY. ISOLATOR TO BE PROVIDED WITHIN 1 MTR. OF THE MOTOR BY OTHERS
  3. FINISH :-



Bolton Gate Co. Limited  
 Waterloo Street  
 Bolton. BL1 2SP  
 Telephone: 01204 871000  
 Facsimile: 01204 871049

TITLE	ARRANGEMENT FOR E.O. INSULATED ROLLING SHUTTERS	C		F	DRAWN:	WORKS ORDER No
SITE		B		E	DATE:	
DATE	REVISION	A		D	CHECKED:	DRAWING NUMBER
		REF	DATE	REF	SCALE:	NTS