

## Pro Visitor Chairs, PRO



The Pro chair's gently arching form, emphasised by a cast aluminium knuckle connecting the arms to the precision tailored upholstery, makes an impression in any office environment.

Pro boasts an assured level of comfort and may be specified as a stackable or non-stackable frame. It is also available with a 4-star base or 5-star base with castors. The Pro chair is the ideal accompanying visitor chair and is equally suited to boardroom, meeting and conference spaces.

**Web link:** [http://www.boss-design.co.uk/creo\\_files/upload/documents/pro\\_brochure.pdf](http://www.boss-design.co.uk/creo_files/upload/documents/pro_brochure.pdf)

**Manufacturer:** Boss Design

**Contact Email:** [sales@boss-design.co.uk](mailto:sales@boss-design.co.uk)

**Contact Telephone:** 1387 455570

### Features

- Fully upholstered in any fabric or leather
- CMHR moulded seat and back foams
- Hard compound polyurethane arm sleeves
- Polished cast aluminium knuckle detail
- Stackable or non-stackable cantilever frame options
- Stackable 3 high



**Warranty and Servicing:** Standard 5 year warranty, please contact us for further information

**Environmental Data**

Statistics based on: Pro Visitor Chair

% of Recycled Content By Weight	% of Recyclable Content By Weight	CO2 produced per 200 employees (Tonnes)	CO2 produced per unit (Tonnes)	CO2 produced per 1000 units (Tonnes)
<b>59</b>	<b>84</b>	<b>0.17</b>	<b>0.034</b>	<b>33.8</b>

**Dimensions**

<b>Pro 4 Star Base</b>	<i>Height</i>	<i>865mm</i>	
	<i>Width</i>	<i>730mm</i>	
	<i>Depth</i>	<i>730mm</i>	
	<i>Seat Height</i>	<i>460mm</i>	
	<i>Seat Depth</i>	<i>470mm</i>	
<b>Pro Cantilever Base</b>	<i>Height</i>	<i>845mm</i>	
	<i>Width</i>	<i>555mm</i>	
	<i>Depth</i>	<i>605mm</i>	
	<i>Seat Height</i>	<i>460mm</i>	
	<i>Seat Depth</i>	<i>470mm</i>	
<b>Pro 5 Star Base</b>	<i>Height</i>	<i>825-925mm</i>	
	<i>Width</i>	<i>555mm</i>	
	<i>Depth</i>	<i>690mm</i>	
	<i>Seat Height</i>	<i>420-520mm</i>	
	<i>Seat Depth</i>	<i>470mm</i>	

**Certification:** BSEN13761 (2002), BSEN13761 (2002)