

Southern Analog (UK manufacture)

Panoramic / Viewfinder

Colours: Aperture, Filter, Flash, Lens, Macro, Process, Range, Reflex

| | |
|--------------------------------|---|
| Construction | Tufted, Textured Loop Pile |
| Face Fibre | Econyl® 100% recycled Type 6 Nylon |
| Antimicrobial | AlphaSan® Built-In Protection |
| Finished Face Weight | 510 gsm |
| Gauge | 47.2 / 10 cm |
| Rows | 40.8 / 10 cm |
| Tuft density | 192,600 / m ² |
| Finished Pile Height | 3.0 mm avg. |
| Standard Backing | 85% Recycled content Polyurethane cushion Available with TractionBack® |
| Nominal Total Thickness | 8.8 mm avg. |
| Tile Size | 50 cm x 50 cm |
| Nominal Total Weight | 3,600 gsm |



PERFORMANCE

| | |
|---|--------------------------------------|
| Flammability (Euroclassification EN13501:1-2002) | Class Cfl - s1 |
| Flammability (Radiant Panel ASTM-E-648) | Class 1 |
| Flammability (Hot metal nut BS4790) | Low radius of Char |
| Use Classification (EN1307) | Class 3 3 Heavy Commercial Use |
| Static Electricity (ISO 6356) | ≤ 2.0 KV, Permanent Conductive Fibre |
| Impact Sound (ISO 140-8) | 32 dB |
| Sound Absorption (ISO 354) | 0.25 Class E |

ENVIRONMENTAL 85% recycled Polyurethane cushion backing
30% recycled content on total product weight
Manufactured using electricity from renewable sources
CRI Green Label Plus certified for indoor air quality

Design Copyright - Milliken & Company

This cushion-back carpet tile product is covered by one or more patents, Publisher applications and/or patents pending.

Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.



1095




Guarantees:


12 year wear guarantee
Lifetime Antistatic guarantee
Latent Defects guarantee

Installation Method:

Monolithic



Brick



Milliken.