


Mini Retractable Loft Ladder...



...ideal for small ceiling openings

The Mini aluminium loft ladder is specially designed for small ceiling openings. It is supplied as a ready to fit unit, consisting of a space-saving aluminium ladder contained within an insulated laminated wooden hatch box.



Key benefits at a glance

- Space-saving retractable loft ladder for small ceiling openings.
- Lightweight and durable aluminium ladder.
- Load capacity of 150kg per step.
- Ease of use.
- Good energy efficiency of 0.80 W/m²K.
- Hatch trap door finished in white on both sides.
- Available in standard sizes or made-to-order, with a range of accessories.
- Available with F30, F30 Plus and F60 fire resistance.

Key features

Material:	Aluminium
Operation:	Spring-assisted retractable ladder
Load capacity:	150kg per step
U-value:	0.80 W/m ² K
Air permeability:	Class 4 certified
Max floor-to-ceiling height:	3.25m
Quality:	Compliant to EN 14975 (DN 4570)
Warranty:	2-year full warranty and 10-year parts warranty



The Mini is manufactured from light-weight aluminium profile

Overview

The Mini aluminium loft ladder is specially designed for small ceiling openings. It is supplied as a ready to fit unit, consisting of a space-saving retractable aluminium ladder contained within, and attached to, a laminated wooden hatch box. The insulated trapdoor provides good energy efficiency and both sides are finished in white for improved aesthetics. It comes assembled with a telescopic handrail for comfort and safety.

Standard features

- Retractable (concertina) loft ladder
 - Easy to operate.
 - Compact, space-saving design
- Retractable ladder manufactured from aluminium
 - Lightweight
 - Strength
 - Durability
- Load capacity of 150kg per step
- Supplied assembled in a hatch box with insulated trapdoor
 - Trapdoor supplied with a white finish to both sides
 - Standard hatch box height of 240mm, but can be specified for heights of up to 390mm
 - Snap-lock closure mechanism
- Energy efficient (U-value of 0.80 W/m²K, calculated by manufacturer according to DIN EN ISO 6946)
 - Reducing loss of heat and lowering energy costs
- Class 4 air permeability certified
- Available in standard hatch sizes for floor-to-ceiling heights between 2250mm and 2750mm
- Can be made-to-order to meet your exact dimensional requirements, for floor-to-ceiling heights of up to 3250mm (contact us for details)
- Optimal step / tread size for width of ceiling opening
 - Maximum stair width supplied to fit your floor-to-ceiling height and opening width
 - Step width of 280mm (for a 550mm opening width) and 330mm (for opening widths between 600mm and 800mm)
 - Step depth from 80mm

Accessories

- WDL insulation and sealing tape for an airtight connection between the loft ladder hatch box and the building
- Installation/assembly aid
- Close-off lock
- Protective railing for opening
- White wooden cover strip




WDL insulation and sealing tape for an airtight connection between hatch box and ceiling

Dimensions

The Mini is available in a range of standard dimensions:

Part number	A Floor- to- ceiling height (mm)	B Opening length (mm)	C Opening width (mm)	D Case height (mm)	E Set down point (mm)	F Swivel range * (mm)
MIN-2750-1120-600	2750	1120	600	240	1300	1490
MIN-2750-1120-700	2750	1120	700	240	1300	1490
MIN-2750-1200-600	2750	1200	600	240	1300	1490
MIN-2750-1200-700	2750	1200	700	240	1300	1490
MIN-2750-1100-600-F30	2750	1100	600	220	1300	1490
MIN-2750-1100-700-F30	2750	1100	700	220	1300	1490
MIN-2750-1200-600-F30	2750	1200	600	220	1300	1490
MIN-2750-1200-700-F30	2750	1200	700	220	1300	1490
MIN-2750-1100-600-F30P	2750	1100	600	220	1300	1490
MIN-2750-1100-700-F30P	2750	1100	700	220	1300	1490
MIN-2750-1200-600-F30P	2750	1200	600	220	1300	1490
MIN-2750-1200-700-F30P	2750	1200	700	220	1300	1490
MIN-2750-1100-600-F60	2750	1100	600	220	1300	1490
MIN-2750-1100-700-F60	2750	1100	700	220	1300	1490
MIN-2750-1200-600-F60	2750	1200	600	220	1300	1490
MIN-2750-1200-700-F60	2750	1200	700	220	1300	1490

* This is the required minimum clearance in front of the ladder to extend/retract.



If you have specific dimensional requirements, the Mini is available made-to-measure for ceiling openings ranging between 800mm to 1400mm long and 550mm to 800mm wide, and for floor-ceiling heights up to 3.25m. Please contact us for details and to arrange a quotation.

Quality

The Supreme loft ladder is manufactured to EN 14975 (DN 4570).

Supplied with a 2-year full warranty and 10-year parts warranty.

The
preferred
choice



Premier Loft Ladders Ltd

2 Dawson Drive, Trimley St Mary, Felixstowe, IP11 0YW, UK

T: 01394 214413 or 0845 9000 195

F: 01394 214413

E: sales@premierloftladders.com

W: www.premierloftladders.com