


Interface®

World Woven 860

Product definition	Tufted Patterned Level Loop Tile					
Pile Material	100% Recycled Solution Dyed Nylon					
Pile Yarn Weight	575g/m ² ± 5%					
Total Weight	4211g/m ² ± 5%					
Pile Height	2.5 ± 0.5 mm					
Total Thickness	6.0 mm ± 0.5 mm					
Gauge/Ends per 10cm	1/10 - 39.4					
Tufts per m2	149,720 ± 5%					
Backing Type	Graphlex®					
Wear Classification	EN 1307 33 Heavy Contract					
Radiant panel	(EN ISO 9239/1) Cfl S1 (EN ISO 13501)					
Dimensional Stability	≤ 0.2% (ISO 2551 / EN 986)					
Impact Sound Insulation (ΔLw)	23 dB (EN ISO 10140-3)					
Rating of Sound Absorption	α _w 0.15 (EN ISO 11654)					
Sound Absorption						
125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz	(EN ISO 354)
0.00	0.02	0.04	0.14	0.25	0.27	α _s
Style number	8109	4m ² - 16 Tiles per Box (25cm x 100cm ± 0.2%)				



Interface Europe Ltd reserve the right to change or modify specifications

www.interface.com



Mission Zero:
our promise to eliminate any
negative impact our company
may have on the environment
by the year 2020.