

# Interface®

## World Woven 880

### Product definition

Tufted Patterned Structured Tip Sheared Tile

<b>Pile Material</b>	100% Recycled Solution Dyed Nylon
<b>Pile Yarn Weight</b>	850g/m <sup>2</sup> ± 5%
<b>Total Weight</b>	4304g/m <sup>2</sup> ± 5%
<b>Pile Height</b>	4.1 ± 0.5 mm
<b>Total Thickness</b>	7.7 mm ± 0.5 mm
<b>Gauge/Ends per 10cm</b>	1/10 - 39.4
<b>Tufts per m2</b>	169,420 ± 5%
<b>Backing Type</b>	Graphlex®
<b>Wear Classification</b>	EN 1307 33 Heavy Contract

<b>Radiant panel</b>	(EN ISO 9239/1) Cfl S1 (EN ISO 13501)
<b>Dimensional Stability</b>	≤ 0.2% (ISO 2551 / EN 986)
<b>Impact Sound Insulation (ΔLw)</b>	26 dB (EN ISO 10140-3)
<b>Rating of Sound Absorption</b>	α <sub>w</sub> 0.20 (EN ISO 11654)

### Sound Absorption

<b>125Hz</b>	<b>250Hz</b>	<b>500Hz</b>	<b>1000Hz</b>	<b>2000Hz</b>	<b>4000Hz</b>	(EN ISO 354)
0.02	0.03	0.07	0.22	0.30	0.40	α <sub>s</sub>

<b>Style number</b>	8112	3.5m <sup>2</sup> - 14 Tiles per Box (25cm x 100cm ± 0.2%)
---------------------	------	--

EN 14041

CE

DOP: 1037/123279

textile floor covering

EN 1307

ASHLAR

HERRINGBONE

33

Cfl-S1

05

26 dB

0.20

≥ 7

≥ 2.4

A20BE79E

www.pro-din.info

install with TacTiles®



Interface Europe Ltd reserve the right to change or modify specifications

[www.interface.com](http://www.interface.com)



**Mission Zero:**  
our promise to eliminate any  
negative impact our company  
may have on the environment  
by the year 2020.