

# Interface®

## Collins Cottage

### Product definition

Tapestry Tufted Patterned Structured Loop Tile


<b>Pile Material</b>	100% Recycled Solution Dyed Nylon
<b>Pile Yarn Weight</b>	882 g/m <sup>2</sup> ± 5%
<b>Total Weight</b>	4504g/m <sup>2</sup> ± 5%
<b>Pile Height</b>	3.9 mm ± 0.5 mm
<b>Total Thickness</b>	8.2 mm ± 0.5 mm
<b>Gauge/Ends per 10cm</b>	1/10 - 39.4
<b>Tufts per m2</b>	124,110 ± 5%
<b>Backing Type</b>	Graphlex®
<b>Wear Classification</b>	EN 1307 33 Heavy Contract

<b>Radiant panel</b>	(EN ISO 9239/1) Euroclass Cfl s1 (EN ISO 13501)
<b>Dimensional Stability</b>	≤ 0.2% (ISO 2551/EN 986)
<b>Impact Sound Insulation (ΔLw)</b>	27 dB (EN ISO 10140-3)
<b>Rating of Sound Absorption</b>	α <sub>w</sub> 0.20 (EN ISO 11654)

### Sound Absorption

<b>125Hz</b>	<b>250Hz</b>	<b>500Hz</b>	<b>1000Hz</b>	<b>2000Hz</b>	<b>4000Hz</b>	(EN ISO 354)
0.00	0.06	0.12	0.29	0.38	0.51	α <sub>s</sub>

<b>Style number</b>	8152	4m <sup>2</sup> - 16 Tiles per Box (50 cm x 50 cm ± 0.2%)
---------------------	------	---



Interface Europe Ltd reserve the right to change or modify specifications

[www.interface.com](http://www.interface.com)



**Mission Zero:**  
our promise to eliminate any  
negative impact our company  
may have on the environment  
by the year 2020.