



* Material: AISI 316
chemically descaled and passivated
* Max. working pressure: 8 bar
* Max. temperature pressure: 90° C
* Thermally insulated:
Polyurethane with C.F.C.-free

* Equipments:
- External lining
- Top cover
- Lateral hole with cover
- Control panel with
thermometer and regulating
and safety thermostat

MODEL	male A	male B	male C	male D	male E	male F	male G	female H	female A2	Capacity (liters)	Weight (Kg.)
200	2"	1-1/2"	2"	1"	2"	2"	1"	1/2"	2-1/2"	195	51
300	2"	1-1/2"	2"	1"	2"	2"	1"	1/2"	2-1/2"	287	60
500	2"	1-1/2"	2"	1"	2"	2"	1"	1/2"	2-1/2"	480	91
800	2"	1-1/2"	2"	1-1/4"	2"	2"	1"	1/2"	2-1/2"	792	134
1000	2"	1-1/2"	2"	1-1/4"	2"	2"	1"	1/2"	2-1/2"	990	157

MODEL	A	B	C	D	E	F	G	H
200	Ø 620	1205	308	220	70 ±5	620	928	298
300	Ø 620	1685	308	707		1107	1415	
500	Ø 770	1690	355	616		1016	1371	
800	Ø 950	1840	332	740	100	1140	1472	322
1000	Ø 950	2250		1150		1550	1882	