

# Ecophon Focus™ SQ

*For applications where the minimum possible overall depth of system is required because of limited space or other reasons. The tiles are bonded directly to the soffit surface. Ecophon Focus SQ is installed with a gap between each tile, creating a ceiling with a smooth appearance. The tiles are not demountable.*

*The tiles are manufactured from high density glass wool. The visible surface has an Akutex FT coating and the back of the tile is covered with glass tissue. The edges are painted. The weight is approximately 2,5 kg/m<sup>2</sup>.*

*Ecophon recommends Connect Absorber Glue for a quick and easy installation.*




Salo Library, Salo, Finland


## SYSTEM RANGE




Size, mm	600x600	1200x600
Direct	•	•
Thickness	20	20
Inst. Diag.	M107	M107



Focus SQ tile



Section of Focus SQ system



Focus SQ system




## Acoustic

### Sound Absorption:

Test results according to EN ISO 354. Classification according to EN ISO 11654, and the single value ratings for Noise Reduction Coefficient, NRC and Sound Absorption Average, SAA according to ASTM C 423.

$\alpha_p$  Practical sound absorption coefficient



— Focus SQ 20 mm, 20 mm o.d.s.

o.d.s = overall depth of system

THK mm	o.d.s. mm	$\alpha_p$ Practical sound absorption coefficient						$\alpha_w$	Sound absorption class
		125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz		
20	20	0,05	0,35	0,70	0,95	1,00	1,00	0,65	C

THK mm	AC(1.5) Articulation Class, ASTM E1111, ASTM E1110
20	190



### Accessibility

The tiles are demountable.



### Cleanability

Daily dusting and vacuum cleaning. Weekly wet wiping.



### Visual appearance

White Frost, nearest NCS colour sample S 0500-N, 85% light reflectance (of which more than 99% is diffuse reflection). Retro reflection coefficient 63 mcd/(m²lx). Gloss < 1.



### Influence of climate

The tiles withstand a permanent ambient RH up to 95% at 30°C without sagging, warping or delaminating (ISO 4611).



## Indoor Climate

Certificate / Label

Europe

EN  
13501-1

M1



## Environmental influence

Certificate / Label

Europe

EN  
13501-1

Fully recyclable.



## CO<sub>2</sub>

Kg CO<sub>2</sub> equiv/m<sup>2</sup>

3,42

From EPD in conformity with ISO 14025 / EN 15804



## Fire safety

Country

Standard

Class

Europe

EN 13501-1

A2-s1,d0

The glass wool core of the tiles is tested and classified as non-combustible according to EN ISO 1182.



## Mechanical properties

Additional live load has to be fixed to the soffit.




## Installation

Installed according to installation diagrams, installation guides and drawing aid. For information regarding minimum overall depth of system see quantity specification. Rendered surfaces must have sufficient strength to be able to carry the load imposed by the tiles. If doubts, test gluing should be carried out. The surface should always be dry and clean. For best result the surface should be even, however an acceptable result could be achieved on slightly uneven surfaces.



## CE


The CE marking confirms important product performance such as sound absorption, emissions, fire safety and load bearing capacity. All Ecophon ceiling products are CE marked according to European standard EN13964, and individual product performance is declared in Declaration of Performance (DoP) documents.




© Ecophon Group

## QUANTITY SPECIFICATION (EXCL. WASTAGE)


		Size, mm	
		600x600	1200x600
1	Focus SQ *	2,8/m <sup>2</sup>	1,4/m <sup>2</sup>
2	Connect Absorber glue (0,25 l/m <sup>2</sup> - 0,4 l/m <sup>2</sup> depending on installation conditions) (10 Litres)	as required	as required
Δ Min. overall depth of system: 23 mm		-	-
δ Min. demounting depth: The system is non-demountable		-	-
Cut visible edges should be painted		-	-
* Panel Module size 600x600 (592x592), 1200x600 (1192x592)		-	-



See Quantity specification



Application of glue



Size, mm	Max live load [N]	Min load bearing capacity [N]
600x600	-	-
1200x600	-	-

Live load/load bearing capacity