

# conference partner scope 300.3000 with castors



**frame:**

- rectangular tube
- glides with Teflon™ insert  
chrome, chromium coating min. 0,1 my, nickel alloy min. 13 my

**seat:**

- cushion made of pu cold moulded foam, densiy approx. 68, 40mm thick, strain hardness 13 kp/a
- upholstery beams made of polypropylene.

**backrest:**

- upholstery padsmade of pu cold moulded foam, density 68, 25 mm thick, strain hardness 13 kp/a.
- upholstery beams made of polypropylene

**base:**

- standard:
- five star polished aluminium die cast.

**armrests:**

- optional,
- aluminium with pu inserts

<b>seat height:</b>	=	470 cm
<b>seat width:</b>	=	470 mm
<b>seat depth:</b>	=	480 mm
<b>total depth:</b>		
front egde to outer edge backrest	=	620 mm
<b>backrest dimensions:</b>		
width x height	=	450 x 370 mm
backrest height	=	430 mm
total height bottom to top edge backrest	=	890 mm
<b>diameter base</b>		
300.3000	=	660 mm
<b>castors:</b>		
300.3000	=	50 mm
<b>chairs with armrests:</b>		
inner width	=	520 mm
total width	=	600 mm
height bottom to top edge armrests	=	670 mm
<b>chairs with cushions:</b>		
thickness seat foam	=	40 mm
thickness backrest foam	=	25 mm
<b>weight:</b>		
chair without armrests	=	8 kg
chair with armrests	=	9 kg

