















GEZE TS 5000 ECLINE System – INSTALLATION OPTIONS

Installation options		DOOR CLOSER MOUNTED ON HINGE SIDE		DOOR CLOSER MOUNTED OPPOSITE THE HINGE SIDE	
		DOOR LEAF MOUNTED	FRAME MOUNTED	DOOR LEAF MOUNTED	FRAME MOUNTED
1-leaf	Accessibility in accordance with DIN 18040 up to EN5	TS 5000 ECLINE with - Standard guide rail - ECLINE guide rail - T-Stop guide rail 	TS 5000 L ECLINE with - Standard guide rail - ECLINE guide rail 	TS 5000 L ECLINE with - Standard guide rail BG - ECLINE guide rail BG - T-Stop guide rail BG 	TS 5000 ECLINE with - Standard guide rail BG - ECLINE guide rail BG 
	Electromechanical hold-open	TS 5000 ECLINE with E guide rail 		TS 5000 L ECLINE with E guide rail 	
	Electromechanical hold-open Smoke switch control unit	TS 5000 ECLINE with R guide rail 		TS 5000 L ECLINE with R guide rail 	
2-leaf	Integrated closing sequence control	TS 5000 ECLINE with ISM guide rail 		TS 5000 L ECLINE with ISM guide rail BG 	
	Integrated mechanical closing sequence control Electromechanical hold-open on both sides	TS 5000 ECLINE with E-ISM guide rail 		TS 5000 L ECLINE with E-ISM guide rail BG 	
	Integrated mechanical closing sequence control Electromechanical hold-open on both sides Smoke switch control unit	TS 5000 ECLINE with E-ISM guide rail 		TS 5000 L ECLINE with R-ISM guide rail BG 	



TS 5000 ECLINE

THE INNOVATIVE ALL-ROUND DOOR CLOSER WITH ACCESSIBILITY STRENGTHS

GEZE GmbH
 Reinhold-Vöster-Straße 21-29
 71229 Leonberg
 Deutschland
 Telefon: +49 (0) 7152-203-0
 Telefax: +49 (0) 7152-203-310
 E-Mail: info.de@geze.com
 www.geze.com

0513 ID No. 155152



BEWEGUNG MIT SYSTEM

TS 5000 Ecline

THE INNOVATIVE ALL-ROUND DOOR CLOSER WITH ACCESSIBILITY STRENGTHS



ACCESSIBILITY IS INCREASINGLY BEING SPECIFIED AS A STANDARD REQUIREMENT.

Not only for people with limited mobility. Accessibility provides additional convenience for all who want to open and pass through doors easily and conveniently.

DIN 18040 defines accessible building in Germany. With GEZE's know-how and "Made in Germany" quality, the smoothest running GEZE door closer, TS 5000 Ecline, fulfils this standard even up to closing force EN 5 - on **single- and double-leaf doors with up to 1250 millimetre door width.**

The TS 5000 Ecline (short for: "easyline") can be combined with all GEZE guide rails and all hold-open systems.

Single-leaf doors can be opened even easier with the TS 5000 Ecline and the Ecline guide rail. With this solution the clever door closer also fulfils the recommendations of the technical report DIN SPEC 1104.



"THE GGT SEAL CERTIFIES THAT THE TS 5000 ECLINE WITH GUIDE RAIL HAS A HIGH DEGREE OF FUNCTIONALITY AND USER CONVENIENCE. DOORS OPEN EASILY AND CONVENIENTLY!"

THE ADVANTAGES OF THE TS 5000 ECLINE AT A GLANCE

- **One for all**

Can be combined with all GEZE guide rails and hold-open systems.

- **Accessibility and safety**

Achieves the high closing force EN 5 while complying with the requirements of DIN 18040.

Doors with door leaf widths up to 1250 millimetres and double-leaf doors can provide accessibility according to according to DIN 18040.

- **Even more convenience at single-leaf doors**

In combination with the Ecline guide rail doors open even more conveniently.

- **Always the right choice**

If forceful closing is required in a use case, e.g. on external doors, the opening support in the Ecline guide rail can be switched off.

- **Functional convenience and easy to install**

Maintenance and installation are easy and convenient – just like all GEZE door closer systems.

Due to the standard TS 5000 drilling pattern, the TS 5000 Ecline closer system is easy to retrofit and is optionally available with mechanical hold-open.

